

SAFETY DATA SHEET

according to 1907/2006/EC

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

JohnsonDiversey

JohnsonDiversey UK Limited

Weston Favell Centre Northampton NN3 8PD Tel 01604 405311 Fax 01604 406809 Emergency Call 0800 052 0185

E-Mail: MSDSinfoUK@johnsondiversey.com

Clearance Code
R63299

JD BOURNE TRAFFIC LIQUID WAX
Professional floor finish

Product Code
MSDSGB6763

TO :

2. HAZARDS IDENTIFICATION

Flammable.

Harmful - May cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

3. COMPOSITION / INFORMATION ON INGREDIENTS.

CAS No	EINECS No			
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy	Xn: R10-65-66	(>30%)

Full text of risk phrases are given in section 16.

4. FIRST AID MEASURES

Eyes : Rinse immediately with plenty of water, holding the eyelids open and seek medical advice if effects persist.

Inhalation : Remove from source of exposure. Seek medical advice if effects persist.

Skin : Wash thoroughly with soap and water.

Ingestion : Remove product from mouth, give the casualty a small quantity of water to drink and seek medical advice. Do not induce vomiting.

5. FIRE FIGHTING MEASURES

FLAMMABLE - In the event of a fire use dry chemicals, foam or fine water spray. May evolve harmful and noxious fumes if involved in a fire. Firefighters should wear self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Wear suitable protective clothing including gloves and eye/face protection. Hose away with plenty of water diluting to at least 1% w/v (10 g/litre) unless this would contaminate a water course or vegetation, in which case either collect, dilute as earlier and pour down wastewater drain (foul sewer) or absorb onto dry sand or similar material and dispose of safely as commercial waste.

7. HANDLING & STORAGE

Avoid contact with skin, eyes and clothing. Always ensure good ventilation when using this product. Keep away from sources of ignition - do not smoke. Protect against electrostatic charges. Do not mix with any other chemicals other than as advised by your JohnsonDiversey representative.

Store upright in original closed containers in a cool place.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Hand : Use gloves resistant to organic solvents.

Eyes : Personal protection is not normally required unless a risk assessment indicates the need for it.

Skin : Wear normal workware overalls or coat.

Respiration : Respiratory protection should normally be achieved through product containment, extract ventilation or other suitable engineering techniques.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance :	Pale yellow liquid	Odour :	Slightly perfumed
		Solubility :	Not miscible in water

Flammability :	Flammable	Flash Point :	40°C (Pensky M. cc). This product with a flashpoint between 21°C & 61°C does support combustion.
Density :	0.77 g/cm³	Explosive properties :	Product is not explosive

10. STABILITY & REACTIVITY

Provided the product is stored in accordance with the approved guidelines there are no known hazardous decomposition products.

11. TOXICOLOGICAL INFORMATION

Eyes :	Unlikely to be irritant in normal use.
Skin :	Repeated exposure may cause skin dryness or cracking.
Inhalation :	Unlikely to be irritant in normal use.
Ingestion :	Harmful: May cause lung damage if swallowed.

12. ECOLOGICAL INFORMATION

When used for its intended purpose this product should not cause adverse effects in the environment.

13. DISPOSAL CONSIDERATIONS

This product does not contain any prescribed substance under the Environmental Protection Act (Prescribed Processes and Substances) Regulations 1991 and is not classified as special waste under the Control of Substances (Special Waste) Regulations 1996, but is classified as controlled waste under the Environmental Protection Act 1990. Do not pour down a wastewater drain (foul sewer) or contaminate water. Dispose of safely as commercial waste.

European waste catalogue 16 03 05 Organic wastes containing dangerous substances.

14. TRANSPORT INFORMATION

EEC Regulation :	HYDROCARBONS, LIQUID, NOS, (NAPTHA), UN3295, Class 3, PG III
IMDG/UN :	HYDROCARBONS, LIQUID, NOS, (NAPTHA), UN3295, Class 3, PG III
RID/ADR :	HYDROCARBONS, LIQUID, NOS, (NAPTHA), UN3295, Class 3, PG III
ICAO/IATA :	Passenger Aircraft: 309, Y309 Cargo Aircraft 310

15. REGULATORY INFORMATION

Hazard symbol :	Xn, HARMFUL, Contains naptha (petroleum), hydrotreated heavy.
Risk phrases :	R10 Flammable. R65 Harmful: May cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.
Safety phrases :	S23 Do not breathe spray. S24 Avoid contact with skin. S51 Use only in well-ventilated areas. S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Handle and apply only as recommended, for full information see product information sheet.

Internal Reference:- MSDSGB6763-01 (17-Dec-2009), FM004512

Text of risk phrases associated with ingredients in section 3.

R10 Flammable.
R65 Harmful: May cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
Change made to section 6, 9, 14 and 16.