

AUTO GLASSWASH

Page: 1

Compilation date: 01/07/2015

Revision date: 08/03/2018

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: AUTO GLASSWASH

Product code: 77/01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaning product for professional use.

1.3. Details of the supplier of the safety data sheet

Company name: Kelher Supplies Ltd 3 Hawkshead Road Croft Business Park Bromborough Wirral CH62 3RJ Tel: 0151 334 9996 Fax: 0151 334 8882 Email: info@kelhersupplies.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words:DangerPrecautionary statements:P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

AUTO GLASSWASH

Rinse skin with water.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM XYLENE SULPHONATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-090-9	1300-72-7	-	Eye Irrit. 2: H319	10-30%
1-HYDROXYE	THYLIDENE)BIS-F	PHOSPHONIC ACID TETRASODIUM S	ALT	
223-267-7	3794-83-0	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
	OXIDE			
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%

Section 4: First aid measures

4.1. Description of first aid measures				
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.			
	Drench the affected skin with running water for 10 minutes or longer if substance is still			
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.			
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist			
	examination.			
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10			
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.			
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital			
	as soon as possible.			
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If			
	unconscious and breathing is OK, place in the recovery position. If conscious, ensure			
	the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and			
	provide oxygen if available. Transfer to hospital as soon as possible.			
4.2. Most important symptoms	and effects, both acute and delayed			
Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.			
	Corneal burns may occur. May cause permanent damage.			
-	Corrosive burns may appear around the lips. Blood may be vomited. There may be			
ingestion.	bleeding from the mouth or nose.			

AUTO GLASSWASH

	Page:	3
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may	
	cause coughing or wheezing.	
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.	
4.3. Indication of any immediat	e medical attention and special treatment needed	
Immediate / special treatment:	Eye bathing equipment should be available on the premises.	
Section 5: Fire-fighting measu	res	
5.1. Extinguishing media		
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray	_
	to cool containers.	
5.2. Special hazards arising fro	m the substance or mixture	
Exposure hazards:	Corrosive. In combustion emits toxic fumes.	
5.3. Advice for fire-fighters		
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact	
	with skin and eyes.	
Section 6: Accidental release n	neasures	
6.1. Personal precautions, prot	tective equipment and emergency procedures	
Personal precautions:	Notify the police and fire brigade immediately. If outside keep bystanders upwind and	
-	away from danger point. Mark out the contaminated area with signs and prevent access	
	to unauthorised personnel. Do not attempt to take action without suitable protective	
	clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the	
	escape of liquid.	
6.2. Environmental precautions	\$	
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.	

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

AUTO GLASSWASH

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1	2	-	-

Respirable dust

DNEL/PNEC Values

Hazardous ingredients:

SODIUM HYDROXIDE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	1	Consumers	Local
DNEL	Inhalation	1	Workers	Local

8.2. Exposure controls

Engineering measures:	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures,
	local exhaust ventilation or other engineering controls to keep worker exposure to
	airborne contaminants below any recommended or statutory limits.

- **Respiratory protection:** Use aproperly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
 - Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove
 - **Eye protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless

AUTO GLASSWASH

the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

- **Skin protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	Colourless
Odour:	Characteristic odour
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Soluble
Viscosity:	Non-viscous
Flash point℃:	>70

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

pH: 12-13

AUTO GLASSWASH

Page: 6

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

AUTO GLASSWASH

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Disposal of packaging:	The generation of waste should be avoided or minimised wherever possible. Waste
	packaging should be recycled. Incineration or landfill should only be considered when
	recycling is not feasible.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1824

14.2. UN proper shipping name

Shipping name: SODIUM HYDROXIDE SOLUTION

(SODIUM HYDROXIDE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

AUTO GLASSWASH

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.